



REV 版本	DESCRIPTION 描述	DATE 日期
A00	First issue	Apr-25-2007



VIEWING DIRECTION



PIN	1	2	3	4	5	6	7	8
CONNECTION	VSS	VDD	V0	RS	RW	E	DB0	DB1
PIN	9	10	11	12	13	14	15	16
CONNECTION	DB2	DB3	DB4	DB5	DB6	DB7	LEDA	LEDK

Specification:

- 1). Driving: Duty:1/16, Bias:1/5, VLCD:3.3V, VDD:3.3V
- 2). Viewing Direction: 6 O'clock
- 3). Display mode: FSTN/Positive/Transflective
- 4). Operating temp.: 0°C~+50°C  
Storage temp.: -10°C~+60°C
- 5). IC: S6A0069-22
- 6). Backlight: Side, Green
- 7). Dimensions with mark "\*" are important, with mark "()" are referenced
- 8). All the raw materials are RoHS compliant

**深圳市秋田视佳实业有限公司**  
SHENZHEN AV/DISPLAY CO.,LTD.

PART NO: 零件编号	C/D结构图	PROJECTION 三角法	MODEL NUMBER 模组型号	SCALE 比例	FTT 适应图面
FAV-ABC016002E47-R-00			ABC016002E47-TRG-R	SHEET: 页次	1 OF 1
				GENERAL TOL: 公差	±0.3
				APPROVALS 签字	DATE 日期
				CHK: 日期	
				DWN: 日期	

DO NOT SCALE THIS DRAWING.