



REV 版本	DESCRIPTION 描述	DATE 日期
A00	First issue	JAN-17-2007




VIEWING DIRECTION






PIN	1	2	3	4	5	6	7	8
CONNECTION	VSS	VDD	V0	RS	RW	E	DB0	DB1
PIN	9	10	11	12	13	14	15	16
CONNECTION	DB2	DB3	DB4	DB5	DB6	DB7	LEDA	LEDK

- Specification:
- 1). Driving: Duty:1/16, Bias:1/5, VLCD:4.5V, VDD:5.0V
 - 2). Viewing Direction: 6 O'clock
 - 3). Display mode: STN/Negative/Transmissive/Blue
 - 4). Operating temp.: -20°C~+70°C
 - 5). Storage temp.: -30°C~+80°C
 - 6). IC: S6A0069X01-COCX
 - 7). Backlight: Side White
 - 8). Dimensions with mark "*" are important, with mark "()" are referenced
 - 9). Meet for RoHS



深圳市秋田视佳实业有限公司
SHENZHEN AVIDISPLAY CO.,LTD.

PART NO: 零件编号	C/D结构图	PROJECTION 三角法	MODEL NUMBER 模组型号	SCALE 比例	FIG 适应图面
FAV-ABC016002E01-R-00			ABC016002E01-81W-R	SHEET: 页次	1 OF 1
				GENERAL TOL: 公差	±0.3
				UNIT 单位	mm
				APP: 签字	DATE 日期
				CHK: 签字	
				DWN: 签字	

